

Commercial Smart Mi fare RFID Hotel Room Safe Lock System SP-5HRL Specification:

Features:

- Powersupply: DC6V,4PCSStandardAAAlkalineBattery
- Battery Life: about 1 year, depending on the usage condition.
- Lowvoltagewarning:Voltagelessthan4.8v,therewillbe3soundsandtheredLED light. Thelock stillcan* beunlockedmorethan50times,beforethebatteryis replaced.
- Reliability of card operation: No accident for 5000 times of continuous card operation
- Emergency unlocking: The door can be unlocked by Master card OR Mechanical key even though the deadbolt works under an emergency situation.
- $\bullet \qquad \text{Installation request:} To be installed on the door, with the door thickness between 30 mm and 55 mm. If the door surface is decorated, the distance between the decoration edge to the door edge must be over 95 mm. \\$
- Itisforgedbyzincalloy(stainlesssteelorcopper)once, withhigh security and solidity nature.
- Intellectual ultrathin little core of lock, This makes the breakage to the door as little as possible when making holes.
- $\bullet \qquad \text{Free handle, to prevent the external stress from ruining the internal structure. The working life is long.}$
- Wetest every circuit board to ensure its lifespan.
- Lackofvoltageindicationtoclewusersshouldchangebatteriesintime.
- Emergency Cardsormechanical keysare used to open doors in special situations.
- Preserve the latest 256 records of the door opening circularly. Knowing about the dynamic at any moment.
- Ending the open functions of lost or appointed cards
- Soor thickness:30-55mm



Spec:

Material	inner quality steel plate outer 304 stainless steel
Mortise	U.S Mortise with 5 Latches
Power supply	4AA Batteries
Low voltage worming	Y
Software	Y
Туре	Hotel management sofware
os	Windows XP/Vista
Card Type	Temic Card
Card reader	Hotel lock encoder
Environment & Verification	
Temperature	-20°G50°C
Humidity	20%-80%
Backup unlock mechanism	Mechanical Key
Dimension (L*W) Warranty:	245MM*75MM
Weight:	2 year 3KG