

Brief Description: Color 1/3 inch Cmos Camera with Night Vision (this specification fit for 10-14 buttons panel, 14buttons without ID)

Main Function:

- Outdoor door unit to solve single building apartment video doorphone solution.
- Capacity: 12 multi-apartments and can be connected to Extension Panel VDS-24XM (24 buttons) to connect more apartments.
- Door bell, Audio / Video communication, unlock with relay solution.
- Flush mounting installation method
- Image device: 1/3" CMOS camera with night vision,700TVL high resolution.
- RF Card Registeration

Specifications & Features:

- Aluminum case
- Image device: 1/3" CMOS camera with night vision,700TVL high resolution.
- Maximum wiring distance: 50meters with 22AWG, 0.65mm 4 wires. 100meters with coaxial 75ohm cable for video wire.
- Wiring: 4 wires
- Communication ways: Synchronous communications
- Scene Illumination: 0.1 Lux(300mm from the camera)
- Image angle: Horizontal 68° vertical: 55°
- Angular Adjust: full angle with 13° adjustment for installation.
- Ambient Humidity: 45% ~ 95%
- Ambient Temperature: -20°C-- +70°C
- Video Signal: 1Vp-p 75Ω, PAL or NTSC
- Power sources: DC 12V 1A adapter
- Panel Dimension: 250*142*10mm



Suprema Security Europe Tom Welsstraat 6. 1336CP. Almere. Netherlands